

## fosera<sub>®</sub> COMMLIGHT

The fosera. COMMLIGHT brings light everywhere. It's available in two version: all-night, giving continues light at the highest brightness level and the smartversion which detects with a motion sensor all movements and increase the brightness level when it is really needed.



SIMPLE AND POWERFUL

[38] [38]



INTEGRATED SOLAR PANEL AND BATTERY

**C**MMLIGHT



SMART-VERSION WITH MOTION SENSOR OR **ALL-NIGHT** 

fosera <sub>®</sub> COMMLIGHT	SUNBEAM	SUNRISE	SUNSHINE
LED lumens output (configurable)	800 - 1000 lm	1600 - 2000 lm	3200 - 4000 lm
LED efficiency	150-170 lm/W		
LED Color temperature	CCT range available from 4000 - 6500 K		
LED light distribution	Asymmetric Batwing <sup>1</sup> ; other options based on order volume		
LED operation		Constant current controlle	d
LED Life-time	Minimum of 70,000 hours		
Motion sensing technology options	Infra-red sensor**		
Battery capacity all-night brightness	12.8 Ah	27 Ah	50 Ah***
@13.2V smart brightness	6.4 Ah	12.8 Ah	27 Ah
Battery technology	Lithium-Iron-Phosphate (LiFePO4) with MPPT charge control		
Enclosure	IP65 rated with alur	minium structure & passive	e-cooled battery box
Operation range	-20°C to +55°C ambi	ent; Wind-speed up-to 12	0 km/h; RH up-to 95%
Mounting method	Easy vertical	clamp-on to poles with an	ti-theft screws
Recommended mounting height	4-5 m	4-6 m	5-7 m
Warranty	3 years; extendable to 5 years**		
SOLAR PANEL			
all-night brightness	20 + 20* W	20 + 40* W	20 + 80* W
Solar-PV smart brightness	20 W	20 + 20* W	20 + 40* W
	' integrated PV module incli	ned at 10°. Additional mod	ules can be tilted

Daily operation hours	12 hours with automatic dusk till dawn control
Autonomy days	2-3 days with minimum solar insolation of 3.5 kWh/m²

Refers to additional external module that can be tilted. \*\* Additional cost apply





<sup>\*\*\*</sup> Subject to change